



- NOTES:**
1. CONSTRUCTION TO FOLLOW ALL GOVERNING CODE REQUIREMENTS BE 3000 PSI OR BETTER, CONCRETE THICKNESS AT LEAST 4" THICK WALLS AND 6" THICK ON FLOOR.
 2. ALL REINFORCEMENT SHALL BE MADE WITH #4 REBAR, 14" IN BOTH DIRECTIONS AND 4" FROM BOTTOM OF SLAB IN TWO DIRECTIONS.
 3. PLACE A SMALL PLASTIC BUCKET INTO BOTTOM OF PIT FOR CONCRETE POURING RECOMMENDED FOR SUMP PUMP PROVISION.
 4. RECOMMENDED WALLS AND SLAB TO BE PAINTED WITH CONCRETE SEALER, 1/2" GAP FILLER BETWEEN SOIL AND CONCRETE FOR WALLS AND FLOOR ONLY.
 5. PIT FLOOR SOIL SHOULD BE COMPACTED AND TERMITTE TREATED.
 6. WALLS MAY BE CONSTRUCTED OF CONCRETE CINDER BLOCKS WITH VERTICAL STEEL BARS AND/OR REBAR DRIVEN TO FULL DEPTH.
 7. SHOP FLOOR CONCRETE SHOULD BE MINIMUM OF 6" THICK (DYNOCOM RECOMMENDS USING 6" THICK).
 8. THESE DRAWINGS ARE INSTALLATION SUGGESTIONS ONLY. SUPPLIER OF THIS DOCUMENT, DYNOCOM INDUSTRIES INC. DOES NOT GUARANTEE THE ACCURACY OF THIS DOCUMENT AND SHALL IN NO MANNER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES RESULTING FROM THE USE OR MISUSE OF THESE INSTALLATION SUGGESTIONS.
 9. COMMON PRACTICE IN ACCORDANCE TO TYPICAL DYNOCOMETER PIT LOCATION.

DYNOCOM INDUSTRIES INC. Automotive Software & Hardware Data Systems	
THIRD ANGLE PROJECTION	TOLERANCES (UNLESS OTHERWISE SPECIFIED) FRACTIONS: 1/32" XXX.4 .001" DECIMALS: .125" HOLE DRILLING: .015" SURFACE FINISH: 325
DESIGNED BY: [REDACTED]	DATE: [REDACTED]
DRAWN BY: [REDACTED]	CHECKED BY: [REDACTED]
DATE: [REDACTED]	DATE: [REDACTED]
NO. OF SHEETS: [REDACTED]	NO. OF SHEETS: [REDACTED]
TITLE: PIT, SINGLE UNIT	SCALE: [REDACTED]
PROJECT NO.: [REDACTED]	PROJECT NO.: [REDACTED]
PROJECT NAME: [REDACTED]	PROJECT NAME: [REDACTED]
PROJECT ADDRESS: [REDACTED]	PROJECT ADDRESS: [REDACTED]
PROJECT CITY: [REDACTED]	PROJECT CITY: [REDACTED]
PROJECT STATE: [REDACTED]	PROJECT STATE: [REDACTED]
PROJECT ZIP: [REDACTED]	PROJECT ZIP: [REDACTED]